

DECLARATION OF PERFORMANCE

According to the Regulation (EU) No.305/2011

No. GABA001/6

SUPERFLUID



- Unique identification code of the product-type:
 GABA001
- 2. Intended use/uses:

According to EN 934-2:T3.1&T3.2, high range water reducing/superplasticizing admixture for concrete

3. Manufacturer:

ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia

4. Authorised representative:

1

5. System or systems of Assessment and Verification of Constancy of Performance (AVCP):

System 2+

6a. Harmonised standard:

EN 934-2:2009+A1:2012

Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd ("Научноизследователски строителен институт – НИСИ" ЕООД, Р. България, София 1618, бул. "Никола Петков" № 86) - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+.







7. Declared performances:

Essential characteristics	Performance	Harmonised technical specification	
Chloride ion content	≤ 0,1% by mass		
Alkali content	≤ 6,5% by mass		
Corrosion behavior	Contains components only from EN 934-1:2008, Annex A.1		
Compressive strength	(at equal consistence T3.1)		
	At 1 day: Test mix ≥ 140 % of control mix	113	112
	At 28 days: Test mix ≥ 115 % of control mix	1:20	1:20
	(at equal w/c ratio T3.2)	2+A	V+6
	At 28 days: Test mix ≥ 90 % of control mix	934-2+A1:2013	2003
Air content	Test mix ≤ 2 % by volume above control mix	MKC EN 9	EN 934-2:2009+A1:2012
Water reduction	In test mix ≥ 12 % compared with control mix		
Consistency	Increase in slump ≥ 120 mm from initial	Σ	□
	(30 ± 10) mm		
	30 min after the addition the consistence of the test mix shall not fall below the value of the initial consistence of the control mix		
Dangerous substances	No performance determined	-	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager,

Blagoja Donchev, Civ. Eng.

Skopje, 16.06.2021







CE MARKING

Annex to DoP No. GABA001/6

ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia

80

GABA001/6

EN 934-2:2009+A1:2012

SUPERFLUID

High range water reducing/superplasticizing admixture for concrete

EN 934-2:T3.1&T3.2

Chloride ion content ≤ 0,1% by mass Alkali content ≤ 6,5% by mass

Corrosion behaviour Contains components only from EN 934-1:2008,

Annex A.1

Compressive strength (at equal consistence T3.1)

> At 1 day: Test mix ≥ 140 % of control mix At 28 days: Test mix ≥ 115 % of control mix

(at equal w/c ratio T3.2)

At 28 days: Test mix ≥ 90 % of control mix

Air content Test mix ≤ 2 % by volume above control mix

Water reduction In test mix ≥ 12 % compared with control mix

Consistency Increase in slump ≥ 120 mm from initial

 $(30 \pm 10) \text{ mm}$

30 min after the addition the consistence of the test

mix shall not fall below the value of the initial

consistence of the control mix

No performance determined Dangerous substances

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS). NOTE

NOISE.

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.



