

# DECLARATION OF PERFORMANCE

According to the Regulation (EU) No.305/2011

No. GKFI0XX/4

---

**HIDROFAS 1.5**

---

**CE**

1. Unique identification code of the product-type:  
**GKFI0XX**  
**EN 15824:ZA.1, decorative external render with uniform texture based on organic binder**
  2. Intended use/uses:  
**This product is used in residential and commercial buildings for decorative and protective finish of exterior surfaces**
  3. Manufacturer:  
**ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia**
  4. Authorised representative:  
 /
  5. System or systems of AVCP:  
**System 4**
  - 6a. Harmonised standard:  
**EN 15824:2009**
- Notified body:  
 /

DECLARATION OF PERFORMANCE




## 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
		MKC EN 15824:2010	EN 15824:2009
Water vapour permeability	<b>V<sub>2</sub> medium</b>	MKC EN 15824:2010	EN 15824:2009
Water absorption	<b>W<sub>2</sub> medium</b>		
Adhesion	<b>≥ 0.3 MPa</b>		
Durability (freeze-thaw resistance)	<b>Permeability rate as specified in EN 1062-3 ≤ 0.5 kg/(m<sup>2</sup>·h<sup>0.5</sup>)</b>		
Thermal conductivity	<b>No performance determined</b>		
Reaction to fire	<b>Class F</b>		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by:  
General Manager,

Zoran Petrovski, Arch.Eng.

Skopje, 23.02.2022

# CE MARKING

Annex to DoP No.GKFI0XX/4

DECLARATION OF PERFORMANCE

CE	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 15 GKFI0XX/4 EN 15824:2009 <b>HIDROFAS 1.5</b> Decorative external render with uniform texture	
Water vapour permeability	<b>V<sub>2</sub> medium</b>
Water absorption	<b>W<sub>2</sub> medium</b>
Adhesion	<b>≥ 0.3 MPa</b>
Durability (freeze-thaw resistance)	<b>Permeability rate as specified in EN 1062-3 ≤ 0.5 kg/(m<sup>2</sup>·h<sup>0.5</sup>)</b>
Thermal conductivity	<b>No performance determined</b>
Reaction to fire	<b>Class F</b>

**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

**NOTE**

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.

