



# DECLARATION OF PERFORMANCE

According to the Regulation (EU) No.305/2011

No. GDCA006/4

**PODING K LIGHT GREEN**



1. Unique identification code of the product:

**GDCA006**

2. Intended use/uses:

**According to EN 13813 CT C50 F7 A9**

**Monolithic finishing coating based on cement, admixtures and high- quality fillers, intended for mechanically loaded floors.**

3. Manufacturer:

**ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia**

4. Authorized representative:

**/**

5. System or systems of AVCP:

**System 4**

- 6a. Harmonized standard:

**EN 13813:2002**

Notified body:

**/**

DECLARATION OF PERFORMANCE





## 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
Reaction to fire:	<b>Class A1</b>	<b>MKC EN 13813:2006</b>	<b>EN 13813:2002</b>
Release of corrosive substances:	<b>CT</b>		
Water permeability:	<b>NPD</b>		
Water vapour permeability:	<b>NPD</b>		
Compressive strength:	<b>C50</b>		
Flexural strength:	<b>F7</b>		
Wear resistance - BÖHME:	<b>A9</b>		
Sound insulation:	<b>NPD</b>		
Sound absorption:	<b>NPD</b>		
Thermal resistance:	<b>NPD</b>		
Chemical resistance:	<b>NPD</b>		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager,



Zoran Petrovski, Arch.Eng.

Skopje, 23.02.2022





# CE MARKING

Annex to DoP No. GDCA006/4

DECLARATION OF PERFORMANCE

CE	
<p>ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 19</p> <p>GDCA006/4</p> <p>EN 13813 CT C50 F7 A9 <b>PODING K LIGHT GREEN</b></p> <p>Monolithic finishing coating based on cement, admixtures and high- quality fillers, intended for mechanically loaded floors</p>	
Reaction to fire:	<b>Class A1</b>
Release of corrosive substances:	<b>CT</b>
Water permeability:	<b>NPD</b>
Water vapour permeability:	<b>NPD</b>
Compressive strength:	<b>C50</b>
Flexural strength:	<b>F7</b>
Wear resistance - BÖHME:	<b>A9</b>
Sound insulation:	<b>NPD</b>
Sound absorption:	<b>NPD</b>
Thermal resistance:	<b>NPD</b>
Chemical resistance:	<b>NPD</b>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

### NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.

