

## **DECLARATION OF PERFORMANCE**

According to Regulation (EU) No.305/2011 No. GBBA001/2

### **INJEKTING K**



- Unique identification code of the product-type: GBBA001
- 2. Intended use/uses:

According to EN 934-4, admixture for cement injection grouts, grouts for prestressing tendons and mixtures for grouting and repair

- Manufacturer:
  ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia
- 4. Authorised representative:
- System or systems of AVCP: System 2+
- 6a. Harmonised standard:

EN 934-4:2009

Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued Certificate of conformity of the factory production control.



#### 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
Fluidity 30 min after mixing	≤ 25 s		
Compressive strength	≥ 30 MPa	6	
Bleeding	≤ 2%	:200	600
Range of volume change at 24 h	-1% ≤ S ≤ 5%	934-4:2009	934-4:2009
Thiocyanate content	Contains components only from EN 934-1:2008, Annex A.1	MKC EN	EN 93
Sulfide content	Contains components only from EN 934-1:2008, Annex A.1	Σ	
Dangerous substances	No performance determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager

Zoran Petrovski, arch.eng.

Skopje, 20.10.2023



# **CE MARKING**

Annex to DoP No. GBBA001/2

 $\epsilon$ 

2032

ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia

23

GBBA001/2

EN 934-4:2009

**INJEKTING K** 

Admixture for cement injection grout

EN 934-4

Fluidity 30 min after mixing ≤ 25 s

Compressive strength ≥ 30 MPa

Bleeding ≤ 2%

Range of volume change at

24 h

-1% ≤ S ≤ 5%

Thiocyanate content Contains components only from EN 934-1:2008,

Annex A.1

Sulfide content Contains components only from EN 934-1:2008,

Annex A.1

Dangerous substances No performance determined

#### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS). **NOTE** 

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.