

## **DECLARATION OF PERFORMANCE**

According Annex III of the Regulation (EU) No.305/2011

No. GDFD001/1

### ADINGPOKS 2

CE

- 1. Unique identification code of the product-type:
  - GDFD00X

-

EN 1504-2:ZA.1f and EN 1504-2:ZA.1g self-leveling flooring for surface protection for concrete and improved physical and chemical resistance

- 2. Intended use/uses:
  - This product is intended for:
    - Physical resistance (Method 5.1 according to EN 1504-9)
    - Chemical resistance (Method 6.1 according to EN 1504-9)
- 3. Manufacturer: ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. Macedonia
- 4. Authorised representative:
- 5. System or systems of AVCP: System 2+
- 6a. Harmonised standard: EN 1504-2:2004

Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control 2032–CPR–11.5C





ш



#### 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
Compressive strength	Class II ≥ 50 N/mm²		
Adhesion strength by pull-off test	≥ 2,0 N/mm <sup>2</sup>		
Capillary absorption and permeability to water	w < 0,1 kg/m <sup>2</sup> ·h <sup>0,5</sup>	1504-2:2006	2004
Abrasion resistance	< 3000 mg		
Impact resistance	Class III ≥ 20 Nm After loading, no cracks, no delamination		1504-2:2004
Resistance to severe chemical attack	Class II: 28 days without pressure ≤ 50% reduction in Shore hardness after treatment in test liquids: petrol; diesel and motor oil; 10% CH₃COOH; 20% H₂SO₄; 20% NaOH; 20% NaCl	MKC EN	EN 1
Reaction to fire	Class F		
Dangerous substances	No performance determined		

#### Appropriate technical documentation and/or specific technical documentation: The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by: AMOHA H D General Manager, ADNHL fille 0 Blagoj Donchev, Civ.Eng. Vat/

Skopje, 19.06.2018







# **CE MARKING**

Annex to DoP No.GDFD00X/1

L CE				
	2032			
ADING AD Skapia				
ADING AD Skopje, Novoselski pat (ul 1409) br.11				
	1060 Skopje, Macedonia			
	17			
	2032–CPR–11.5C			
EN 1504-2:2004				
ADINGPOKS 2				
Self-leveling flooring for surface protection for concrete				
and improved physical and chemical resistance				
Compressive strength	Class II ≥ 50 N/mm²			
Adhesion strength by pull-off test	≥ 2,0 N/mm²			
Capillary absorption and permeability to water	w < 0,1 kg/m²·h <sup>0,5</sup>			
Abrasion resistance	< 3000 mg			
Impact resistance	Class III ≥ 20 Nm			
	After loading, no cracks, no delamination			
Resistance to severe	Class II: 28 days without pressure			
chemical attack	≤ 50% reduction in Shore hardness after treatment in			
	test liquids: petrol; diesel and motor oil;			
	10% CH₃COOH; 20% H₂SO₄; 20% NaOH; 20% NaCl			
Reaction to fire	Class F			
Dangerous substances	No performance determined			

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH) Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

Information and advice on sate handning, storage and usposed or the Gronous products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.



