

DECLARATION OF PERFORMANCE

According Annex III of the Regulation (EU) No.305/2011

No. GKFH00X/1

ш **DECLARATION OF PERFORMANC**



1. Unique identification code of the product-type: **GKFH00X**

EN 15824:ZA.1, decorative external render with uniform texture based on organic binder

- Intended use/uses: This product is used in residential and commercial buildings for decorative and protective finish of exterior surfaces
- 3. Manufacturer: ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. Macedonia
- 4. Authorised representative:

HIDROFAS 1

- 5. System or systems of AVCP: System 4
- 6a. Harmonised standard: EN 15824:2009

Notified body:







7. Declared performances:

Essential Characteristics	Performance Harmonised technical specification		nical
Water vapour permeability	V₂ medium	10	
Water absorption	W ₂ medium	4:20	600
Adhesion	≥ 0.3 MPa	582,	5824:2010 24:2009
Durability (freeze-thaw resistance)	Permeability rate as specified in EN 1062-3 $\leq 0.5 \text{ kg/(m}^2 \cdot h^{0.5})$	EN 1	EN 15824:2009
Thermal conductivity	No performance determined	MKC	ш
Reaction to fire	Class F		

 Appropriate technical documentation and/or specific technical documentation: The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

2

Signed for and on behalf of the manufacturer by:

General manager, TUUL Blagoj Donchev, Civ.Eng.



Skopje, 31.10.2016



DECLARATION OF PERFORMANCE



CE MARKING

Annex to DoP No.GKFH00X/1

Γ			
	(F		
	2032		
	2002		
	ADING AD Skopje,		
	Novoselski pat (ul 1409) br.11		
	1060 Skopje, Macedonia		
	15		
EN 15824:2009			
	HIDROFAS 1		
Decor	rative external render with uniform texture		
Water vapour permeability	V ₂ medium		
Water absorption	W₂ medium		
Adhesion	≥ 0.3 MPa		
Durability (freeze-thaw resistance)	Permeability rate as specified in EN 1062-3 ≤ 0.5 kg/(m ² ·h ^{0.5})		
Thermal conductivity	No performance determined		
Reaction to fire	Class F		

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH) Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

Information and advice on sate framound, storage and unspose or the distinct products are diverse and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.



