

DECLARATION OF PERFORMANCE

According Annex III of the Regulation (EU) No.305/2011

No. GJBA001/1

DECLARATION OF PERFORMANCE

HIDROGLET-F

CE

1. Unique identification code of the product-type:
GJBA001
EN 998-1:ZA.1, general purpose rendering mortar
 2. Intended use/uses:
This product is used for smoothing exterior and interior wall and ceiling surfaces
 3. Manufacturer:
ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. Macedonia
 4. Authorised representative:
 /
 5. System or systems of AVCP:
System 4
 - 6a. Harmonised standard:
EN 998-1:2010
- Notified body:
 /

7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
		MKC EN 998-1:2013	EN 998-1:2010
Compressive strength	CS IV ($\geq 6 \text{ N/mm}^2$)	MKC EN 998-1:2013	EN 998-1:2010
Capillary water absorption	W_1		
Water vapour diffusion coef.	$\mu \leq 15$		
Adhesion	$> 0.5 \text{ MPa}$; FP-B		
Thermal conductivity	$\lambda=0.44 \text{ W/mK}$		
Reaction to fire	Class A1		

8. Appropriate technical documentation and/or specific technical documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by:
General manager,





Blagoj Donchev, Civ.Eng.

Skopje, 31.10.2016

CE MARKING

Annex to DoP No. GJBA001/1

DECLARATION OF PERFORMANCE

 2032	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, Macedonia 15 EN 998-1:2010 HIDROGLET F General purpose rendering mortar	
Compressive strength	CS IV ($\geq 6 \text{ N/mm}^2$)
Capillary water absorption	W₁
Water vapour diffusion coef.	$\mu \leq 15$
Adhesion	> 0.5 MPa; FP-B
Thermal conductivity	$\lambda=0.44 \text{ W/mK}$
Reaction to fire	Class A1

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.