

## DECLARATION OF PERFORMANCE

According to Regulation (EU) No. 574/2014,  
which refers to Annex III of the Regulation (EU) No.305/2011

No. GFAA001/4

DECLARATION OF PERFORMANCE

---

**HIDROMAL**

**CE**

---

1. Unique identification code of the product:  
**GFAA001**
2. Intended use/uses:  
**According to EN 1504-2:ZA.1e, rigid waterproofing, for surface protection of concrete and moisture control.**  
**This product is intended for:**
  - **Moisture control (Method 2.2 according to EN 1504-9) and**
  - **Increasing resistivity by limiting moisture content (Method 8.2 according to EN 1504-9)**
3. Manufacturer:  
**ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia**
4. Authorised representative:  
/
5. System or systems of AVCP:  
**System 2+**
- 6a. Harmonised standard:  
**EN 1504-2:2004**

Notified body:

**Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control 2032-CPR-11.5D**


## 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
		MKC EN 1504-2:2006	EN 1504-2:2004
Permeability to water vapour	<b>Class I, <math>S_D &lt; 5 \text{ m}</math></b>	<b>MKC EN 1504-2:2006</b>	<b>EN 1504-2:2004</b>
Capillary absorption and permeability to water	<b><math>w &lt; 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}</math></b>		
Adhesion strength by pull-off test	<b><math>\geq 1,0 \text{ N/mm}^2</math></b>		
Reaction to fire	<b>Class A</b>		
Dangerous substances	<b>No performance determined</b>		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 574/2014 which refers to Annex III of the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:  
General Manager,




  
Blagoj Donchev, Civ.Eng.

Skopje, 11.11.2019

# CE MARKING

Annex to DoP No. GFAA001/4

DECLARATION OF PERFORMANCE

 2032	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 17 GFAA001/4 EN 1504-2:2004 <b>HIDROMAL</b> Rigid waterproofing, for surface protection of concrete and moisture control	
Permeability to water vapour	<b>Class I, <math>S_D &lt; 5 \text{ m}</math></b>
Capillary absorption and permeability to water	<b><math>w &lt; 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}</math></b>
Adhesion strength by pull-off test	<b><math>\geq 1,0 \text{ N/mm}^2</math></b>
Reaction to fire	<b>Class A</b>
Dangerous substances	<b>No performance determined</b>

**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

**NOTE**

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.

