

## **DECLARATION OF PERFORMANCE**

According to Regulation (EU) No. 574/2014, which refers to Annex III of the Regulation (EU) No.305/2011

No. GCBH001/5

## REPARATUR GLET

 $\epsilon$ 

 Unique identification code of the product: GCBH001

2. Intended use/uses:

According to EN 1504-3:ZA.1, concrete repair product for non-structural repair – mortar based on hydraulic cement and polymer additive (PCC).

This product is intended for:

- Concrete restoration by applying mortar by hand (Method 3.1 according to EN 1504-9)
- Increasing cover to reinforcement with additional cementitious mortar or concrete (Method 7.1 according to EN 1504-9)
- 3. Manufacturer:

ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia

4. Authorised representative:

1

5. System or systems of AVCP:

System 2+

6a. Harmonised standard:

EN 1504-3:2005

Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control 2032–CPR–11.5E







## 7. Declared performances:

Essential Characteristics	Performance	techr	Harmonised technical specification	
Compressive strength	≥ 15 N/mm² (class R2)			
Chloride ion content	≤ 0,05%			
Adhesive bond	≥ 0,8 N/mm²	90		
Restrained shrinkage/expansion	Bond strength after test ≥ 0,8 N/mm²	1504-3:2006	EN 1504-3:2005	
Thermal compatibility: Freeze-thaw cycling with de-icing salt immersion	Bond strength after 50 cycles ≥ 0,8 N/mm <sup>2</sup>	Z		
Capillary absorption	≤ 0,5 kg/m <sup>2</sup> · h <sup>0,5</sup>	MKC	_	
Reaction to fire	Class A1			
Dangerous substances	No performance determined			

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 574/2014 which refers to Annex III of the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager,

Blagoja Donchev, Civ.Eng.

Skopje, 16.12.2020







## **CE MARKING**

Annex to DoP No.GCBH001/5

ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia

17

GCBH001/5

EN 1504-3:2005

**REPARATUR GLET** 

Concrete repair product for non-structural repair mortar based on hydraulic cement and polymer additive (PCC)

Compressive strength ≥ 15 N/mm<sup>2</sup> (class R2)

Chloride ion content ≤ 0,05%

Adhesive bond ≥ 0,8 N/mm<sup>2</sup>

Restrained Bond strength after test

shrinkage/expansion ≥ 0,8 N/mm<sup>2</sup>

Thermal compatibility: Bond strength after 50 cycles

Freeze-thaw cycling with de-

icing salt immersion

≥ 0,8 N/mm<sup>2</sup>

 $\leq$  0,5 kg/m<sup>2</sup> · h<sup>0,5</sup> Capillary absorption

Reaction to fire Class A1

Dangerous substances No performance determined

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)
Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

NOTE
The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.



