

## **DECLARATION OF PERFORMANCE**

According to Regulation (EU) No. 574/2014, which refers to Annex III of the Regulation (EU) No.305/2011

No. GACC001/4

### SUPERFLUID 21F

CE

- 1. Unique identification code of the product-type: **GACC001**
- Intended use/uses: According to EN 934-2:T7, hardening accelerating admixture for concrete
- 3. Manufacturer: ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia
- 4. Authorised representative:
- 5. System or systems of AVCP: System 2+
- 6a. Harmonised standard: EN 934-2:2009+A1:2012

#### Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control 2032–CPR–08.40C







#### 7. Declared performances:

	C		
l			
1			
ì			
ł			

Essential characteristics	Performance		Harmonised technical specification	
Chloride ion content	≤ 0,1% by mass			
Alkali content	≤ 2,0% by mass			
Corrosion behavior	Contains components only from EN 934-1:2008, Annex A.1			
Compressive strength	(at equal consistence - T7)	934-2+A1:2013	2012	
	At 20° C and 24 h: test mix ≥ 120 % of control mix	A1:2	A1::	
	At 20° C and 28 days: test mix $\ge$ 90 % of control mix	-2+1	·+60	
	At 5° C and 48 h: test mix ≥ 130 % of control mix	934	:20(	
Air content	Test mix ≤ 2 % by volume above control mix	N	934-2:2009+A1:2012	
Hardening time/	(at equal consistence - T7)	MKC	6 N U	
strength development	At 20° C and 24 h: test mix ≥ 120 % of control mix	2	ш	
	At 20° C and 28 days: test mix $\ge$ 90 % of control mix			
	At 5° C and 48 h: test mix ≥ 130 % of control mix			
Dangerous substances	No performance determined			

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 574/2014 which refers to Annex III of the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by: AMOHA H DO General Manager, KO Blagoj Donchev, Civ.Eng. Walt \*

Skopje, 10.12.2019







# **CE MARKING**

Annex to DoP No. GACC001/4

	(		
	2032		
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 08			
GACC001/4			
EN 934-2:2009+A1:2012			
Harc	SUPERFLUID 21F dening accelerating admixture for concrete EN 934-2:T7		
Chloride ion content	≤0,1% by mass		
Alkali content	≤ 2,0% by mass		
Corrosion behaviour	Contains components only from EN 934-1:2008, Annex A.1		
Compressive strength	<u>(at equal consistence - T7)</u>		
	At 20° C and 24 h: test mix ≥ 120 % of control mix		
	At 20° C and 28 days: test mix ≥ 90 % of control mix		
	At 5° C and 48 h: test mix ≥ 130 % of control mix		
Air content	Test mix ≤ 2 % by volume above control mix		
Hardening time/	<u>(at equal consistence - T7)</u>		
strength development	At 20° C and 24 h: test mix ≥ 120 % of control mix		
	At 20° C and 28 days: test mix ≥ 90 % of control mix		
	At 5° C and 48 h: test mix ≥ 130 % of control mix		
Dangerous substances	No performance determined		

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH) Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

NOTE The information and events of such tanking, we get an experience in an event of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.



