

# SOLVENT - P

*Solvent for the dilution of methacrylic systems.*

## FIELD OF APPLICATION

For the regulation of viscosity in application products based on methacrylic resins (ADINGMARKER - P, Adingkolor - RF Adingkolor - BP, Plamal - 3D expansive, Plamal - 3D varnish). It is also used for cleaning tools used in constructing methacrylic and epoxy resin-based systems.

## PROPERTIES

- Easily volatile liquid
- Characteristic scent

## TECHNICAL FEATURES

Property	Declared value
Appearance	Colourless liquid
Density	0,85-0,9 g/cm <sup>3</sup>

## APPLICATION

Solvent – P is dosed in accordance with the dosing limits for each product, with constant stirring until it's completely homogenised. In this manner optimal applicative viscosity of products is achieved.

## PACKING

Metal containers of 1kg and 4 kg

## STORAGE

In its original sealed packaging, in dry premises, at a temperature between 5°C and 30°C. Keep away from sources of heat/sparks.  
 SHELF LIFE: 12 months.

### **Health hazard:**

Avoid contact of the product with skin or inhalation of the material. In case of accidental contact, if skin is contaminated with the material, the contaminated areas should be immediately washed with water and soap. If the material splashes into the eyes, immediately rinse the eyes with plenty of water and seek medical advice. Wear protective gloves, clothing, and protection for your eyes and face. Further information is provided in the safety sheet of the product.

### **Fire:**

Solvent-P is flammable. Further information is provided in the Safety sheet of the product.

### **Cleaning and discarding:**

The old and used packing should be discarded in accordance with local guidelines and regulations for that type of waste.