

ADING AD
1000 SKOPJE, R. MAKEDONIJA
Novoselski pat bb

MATERIAL SAFETY DATA SHEET

ISSUE 1.0

DATE :11.01.2008

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **ANTI-KOROZIN-BR**
Product use: Anti-corrosive coating for concrete protection based on synthetic resins and solvents
Manufacturer/Supplier: ADING A.D
Address/telephone no: ADING AD, Novoselski pat bb
Skopje,R.Macedonia
Tel no. ++ 389 2 20 34-800
+ 389 2 20 34-853, 20 34-822
+ 389 2 20 34-821,20 34- 850
fax: + 389 2 20 34-821,20 34- 850
E-mail: ading@t-home.mk
Web site: www.ading.com.mk

2.CHEMICAL COMPOSITION/INFORMATION OF THE COMPONENTS

CHEMICAL COMPOSITION:	CAS/EINECS	Concentration	Classification	Risk phrases
Acrylate resin		20-40 %	X,N	R10;R20/21/22;R52

3. HAZARD IDENTIFICATION

Main hazards: Combustible
Harmful by inhalation, swallowing and skin contact
Harmful to aquatic species

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting because of risk of aspiration. Rinse mouth with water, give copious amounts of water and seek medical advice.
Eye contact: Immediately flood the eye with plenty of water ,holding the eye open.
Obtain medical attention
Skin contact: Wash skin with soap and water.
Remove contaminated clothing as washing proceeds.
Obtain medical attention if irritation occurs
Health care facilities: Provide pure water for flooding of eyes/skin.
Medical recommendation: Provide symptomatic medical treatment

5. FIRE FIGHTING MEASURES

Extinguishing media: Use foam, dry chemical, carbon dioxide.
Extinguishing media-not suitable Do not use water jet
Protective equipment for fire-fighting: Wear protective clothing and self-contained breathing apparatus.
Cool the containers with water
Special hazards of product: None

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Wear appropriate protective clothing. Advise authorities Keep away the unnecessary personnel.
Clean up methods:	Pump large spillages and dispose the absorbed material according to local regulations. Cover the remainder with inert absorbent, sand and sawdust..
Environmental Precautions:	Disposal according to local regulations. Collect as much as possible in a clear container for disposal

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing
Storage:	Storage area should be cool, dry, ventilated out of direct sunlight Storage temperature should be controlled to between 5 and 25°C Store in the original container securely closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering control measures:	Use of the basic principles of industrial hygiene will enable this material to be used safely. Provide closed containers
Respiratory protection:	If limits are exceeded use an approved equipment
Personal protection:	General protection and precautions
Hand protection:	Wear suitable impervious gloves
Eye protection:	Wear safety glasses
Body protection:	Wear protective clothing
Skin protection:	Wash hands and face before break..

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	white or coloured paste compound
Colour:	per client's wish
Odour:	aromatic
pH:	/
Solubility – water	slight
Dry content:	68±3
Density:	1,2-1,3 g/cm ³ ,DIN 51757,20°C

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions
Conditions to avoid:	Heating and sparking
Hazardous decomposition products:	Oxides of agents, oxygen ,moisture

11. TOXICOLOGICAL INFORMATION

Acute toxicity of fish:	/
Bacteria toxicity:	/
Bio accumulative potential: log P:	Not applicable
Persistence/degradability:	The product is expected to be inherently biodegradable
Eco toxicity:	The material is harmful to aquatic species

12. ECOLOGICAL INFORMATION

Ecologic effects:	Not harmful if handled properly according to instructions
The product is eliminated from water by	the process of absorption of activated coal.
Biology effects:	Fish LC ₅₀ >10000 mg/l

13. DISPOSAL

Methods of disposal: Controlled incineration.
Hazard: Empty the containers which contain solvent vapours, hazardous for fire explosion. Arrange for disposal only via a licensed waste containers (Forbidden removal in domestic waste)

14. TRANSPORT INFORMATION

Classification:
Road:(ADR): UN 1866 RESIN SOLUTION: flammable,3III
Air:(ICAO/IATA): UN 1866 RESIN SOLUTION: flammable,3III
Sea:(MDG/IMO): UN 1866 RESIN SOLUTION: flammable,3III,sea pollutant

15. REGULATORY INFORMATION

Label requirements: Harmful material Harmful to environment



Risk phrases: R 10 flammable
R 20/21/22 -harmful by inhalation, swallowing and skin contact
R 52- harmful to aquatic species

Safety phrases: S 16- keep away from sources of ignition – No smoking
S 15 - keep away from source of heat
S 24- avoid skin contact
S 20/21-when using do not eat or drink or smoke.
S 29 - do not empty in to drains

16. OTHER INFORMATION

Reason for Issue: New format
This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request. All information contained in this MSDS is as accurate and up-to-date as possible. No warranty expressed or implied is made as to its accuracy, reliability or completeness.